

*REQUIREMENTS FOR GLOBE STYLE ADVISOR MAGAZINE



SPECIFICATIONS SUBJECT TO CHANGE VISIT OUR WEBSITE FOR UPDATES


FOR FURTHER ADVERTISING INFORMATION PLEASE VISIT GLOBELINK.CA

UPDATED APRIL 2021

NO BLEED AVAILABLE ON STANDARD PAGES

FULL PAGE


NEW SIZE 9"w x 12.375"D



NEW SIZE
18.5" w x 12.375" d
(RUNS THROUGH GUTTER, CENTRE SPREAD ONLY)

Additional special executions are available, including scent strips and sampling. Please speak with your sales representative for more information.

6 PAGE GATEFOLD OFF COVER



OBC

SA FRONT COVER

9.5"

9.25"

9.125"

INSIDE FRONT COVER

LIVE: 8.75"w x 12.375"d TRIM: 9.25"w x 12.875"d (.125" BLEED ALL SIDES)

GATE PANEL (INSIDE AND OUTSIDE)

LIVE: 8.625"w x 12.375"d TRIM: 9.125"w x 12.875"d (.125" BLEED ALL SIDES)

BACK COVER (INSIDE AND OUTSIDE)

LIVE: 9"w x 12.375"D TRIM: 9.5"w x 12.875"D (.125" BLEED ALL SIDES)

PLEASE NOTE: ALL GATEFOLD EXECUTIONS REQUIRE AN ADDITIONAL 4 WEEKS LEAD TIME FOR SPACE BOOKING AND MATERIAL SUBMISSION.



http://www.globelink.ca/magazines

All ads must be sent to:

adforward.globeandmail.ca

SPECIFICATIONS SUBJECT TO CHANGE VISIT OUR WEBSITE FOR UPDATES

FOR FURTHER ADVERTISING INFORMATION PLEASE VISIT GLOBELINK.CA

REQUIREMENTS FOR GLOBE STYLE ADVISOR MAGAZINE

General information

- Ads must be created at 100% final booked size
- Ad material not sent in at final size may be floated within the ad space or scaled to fit
- The given ad size is the final trim size, there is no bleed allowance
- No trapping, chokes or spreads should be used
- DPS ads must be set up as a single unit
- All colour ads should be accompanied by a colour proof that simulates the intended colour reproduction - without a colour proof The Globe and Mail cannot ensure that the colour reproduces as the client intended or that it was prepared properly for magazine reproduction – a fax, electronic PDF, or printout can only be used for content, not colour accuracy

General requirements for PDF files

- Optimized PDF x1a with thumbnail preview
- Output resolution set to 2400 dpi
- · No compression or resampling
- · Embed all fonts
- All embedded art or images should be high resolution in CMYK (minimum 266 dpi)
- No colour conversion and all colours should be defined as CMYK
- Maximum Ink Density 280%
- We also accept Native Files. TIFF and EPS files need to be embedded or linked and collected with the document

Mechanical specifications

- · Saddle stitched
- · Web offset printing
- 133 Line Screen

For more information or questions, please contact:

Isabelle Cabral

Magazine Production Coordinator 416-585-5444 icabral@globeandmail.com

Peter Bonyun

Manager, Production Operations 416-585-5036 pbonyun@globeandmail.com

auick reference – specifications & genera



